

ON-LINE PC BUTTON DRIPPERS

ClickTif HD



Heavy Duty Pressure-Compensating (PC) & Compensating Non-Leakage (CNL) on-line Button Dripper



APPLICATIONS

- Greenhouses, nurseries, orchards, Vineyards, landscapes and garden plots
- Pulse irrigation and irrigation in soilless conditions
- Prevents surplus drainage in low places (CNL model)

STRUCTURE AND FEATURES

- Heavy Duty range of drippers and accessories in various configurations
- Four dripper design elements minimize clogging:
 1. Protected water inlet
 2. Flushing mechanism of regulating diaphragm
 3. Strong turbulent flow in labyrinth enables continual cleaning and flushing
 4. Large water passages
- Color-coded for identification of discharge and model
- Standard 5 mm tapered outlet for working with connectors or barb outlet for 3/5 tube
- Chemical-resistant, high-grade plastic for precision and durability
- Two models available: PC and CNL (Compensating Non-Leakage)
- Unique “sharp edge” CNL design prevents dirt accumulation and ensures reliable operation under difficult conditions
- 6 different flow rates

COLOR CODE



TECHNICAL DATA

- Nominal discharge: 1.3, 2.0, 3.0, 4.0, 8.0, 12.0 l/h
- Regulating pressure range: 0.5-4.0 bar
- Very low CV
- Minimum recommended working pressure 1.0 Bar
- Non-Leakage (CNL): - Opening pressure: 8.0 m
- Closing pressure: 3.0 m
- Filtration Recommendation: 130 micron (120 mesh)



ClickTif HD Accessories

Drop guide



Catalog no.
802870

Straight labyrinth stake




Catalog no.
802800

Elbow labyrinth stake



Catalog no.
802850



3/5 PVC or PE extension tube stabilizer stake



Stabilizer stake

Catalog no.
6466040000

DROP GUIDE

Use as single outlet for drop guide

LABYRINTH STAKES

Working with multiple outlets:


1. Use labyrinth stakes to improve uniformity
2. Minimum recommended working pressure: 1 bar
3. Maximum recommended flow per outlet: 2.0 l/h

2.5 mm Punch

Special design for comfortable punching and inserting of ClickTif drippers



Catalog no.
897284



2, 4, 8 outlets with
flow control stakes

3/5 mm outlet connectors



Catalog no.
802908

Catalog no.
802920

Catalog no.
802940

Multi-level connectors



Catalog no.
802928

Catalog no.
802948

